

BAAVA - 156VL

Schutz	3,5 Tonnen Fahrzeug	Gerätebefestigung	Ja, durch Verschraubung gesichert
Geschwindigkeit	48 km/h	Mobilität	Ja, mit Rollen vorne und hinten. 50 und 100 mm Durchmesser.
Höhe	815 mm	Versand	Barriere montiert oder auf einem Rack von 5 bis 12.
Radstand	1015 mm	Handhabung	Griffe, Schranken können angehoben werden.
Zwischenraum zwischen den Einheiten	420 mm	Versammlung	Von 1 oder 2 Personen.
Zusatzeinheit	560 mm	Beschilderung	Ja, Reflektorschilder mit Kontaktdaten + Logo bedruckt
Stückgewicht	36 kg je nach Konfiguration.	Reflektierend	Ja, auf Anfrage.
Schwenkgriffe	Ja	Malen	Fixierer + Pulverbeschichtung
Zertifizierung	IWA14 – BSI-PAS68 Typ N1	Verzinkt	Ja, optional
Bremsweg	PAS68: 5,5 Meter bei 48 km/h	Farbe	Gelb / Wahl
Herstellung	Einteilige, geschweißte Stahleinheit	Beenden	Geschliffen
Versteifungen	Ja, 8mm	Haftpflichtversicherung	Ja, dem Risiko gewidmet
Verbindungsstäbe	Ja, 2 zwischen den Einheiten	Gerätegarantie	Ja, lebenslang auf Geräte, 5 Jahre auf Verschleißteile.

Barriers comparison		BAAVA 156VL	MIFRAM MVB3X	MIFRAM MVB2	MIFRAM MVB	BLOCK AXESS BLAX V1	BLOCK AXESS BLAX V2	TITAN BT150	Table based on information available to us at 30/11/2020
<i>International certifications</i>		YES IWA14 - PAS68	YES IWA14 - PAS68	YES IWA14 - PAS68	NOT CERTIFIED	YES IWA14 - PAS68	YES IWA14 - PAS68	YES IWA14 - PAS68	
Width in certification Number of units		2,40 LM 5 units	4,30 LM 9 units	4,44 meters 9 units	NON CERTIFIÉE	4,00 meters 6 units	4,06 meters 7 units	9,00 meters 6 units	Based on crash test videos
Certification category Vehicle weight		N1 3500 Kg	M1 2500 Kg.	M1 2500 Kg	M1 2500 Kg	M1 1470 Kg	N1 3500 Kg	N1 3500 Kg	Based on documentation
Vehicle speed		48 Km/h	48 Km/h	32 / 48 Km/h	??	48 Km/h	48 Km/h	48 Km/h	
Stopping distance PAS68 Stopping distance IWA14		5,50 meters 6,50 meters	9,70 meters 10,90 meters	Undisclosed	Undisclosed	Estimated at + 20 meters	12,10 meters 12,40 meters	10,90 meters 11,80 meters	Based on documentation
Barrier breakage		NO	NO	NO		YES	YES	NO	Based on crash test videos
Does the barrier stay in front of the vehicle during a crash test?		YES	NO	NO	NO	NO	NO	YES	Based on crash test videos
Does the barrier slip during crash tests?		NO	Under the vehicle	Under the vehicle	Yes	The vehicle passes	YES	YES	Based on crash test videos
Safety zone behind the barrier (1 to 2 times the stopping distance in a crash test)		5,50 to 11,00 meters	9,7 to 19,40 meters	Indeterminate	Indeterminate	Indeterminate	12,10 to 24,20 meters	11,00 to 22 meters	Exact stopping distance unknown Safety zone undeterminable
Duration of the guarantee Wearing parts, castors		Lifetime 5 years	??	??	??	??	??	??	??: Duration of guarantee not stated on documents.
Civil liability insurance dedicated to risk		YES	??	??	??	??	??	??	??: Specific insurance not provided on documents